

Pb Free Plating Product

HER4002PR thru HER4012PR



40.0 Ampere Heatsink Dual Doubler Polarity High Efficiency Rectifiers

<p>Features</p> <ul style="list-style-type: none"> ThinkiSemi latest&matured process FRD/FRED Low forward voltage drop High current capability Low reverse leakage current High surge current capability <p>Application</p> <ul style="list-style-type: none"> Automotive Inverters and Solar Inverters Car Audio Amplifiers and Sound Device Systems Plating Power Supply, Motor Control, UPS and SMPS etc. <p>Mechanical Data</p> <ul style="list-style-type: none"> Case: Heatsink TO-247AD/TO-3P Package Outline Epoxy: UL 94V-0 rate flame retardant Terminals: Solderable per MIL-STD-202 method 208 Polarity: As marked on diode body Mounting position: Any Weight: 6.0 gram approximately 	<p>TO-247AD/TO-3P Unit:inch(mm)</p> <p>① ② ③ Case</p> <p>Positive Common Cathode Suffix "PT"</p> <p>① ② ③ Case</p> <p>Negative Common Anode Suffix "PA"</p> <p>① ② ③ Case</p> <p>Doubler Tandem Polarity Suffix "PR"</p> <p>① ② ③ Case</p> <p>Series Tandem Polarity Suffix "PL"</p>
---	---

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Rating at 25°C ambient temperature unless otherwise specified.
 Single phase, half wave, 60Hz, resistive or inductive load.
 For capacitive load, derate current by 20%.

PARAMETER	SYMBOL	HER4002PR	HER4003PR HER4004PR	HER4006PR	HER4008PR	HER4010PR	HER4012PR	UNIT
Maximum Recurrent Peak Reverse Voltage	VRRM	200	400	600	800	1000	1200	V
Maximum RMS Voltage	VRMS	140	280	420	560	700	840	V
Maximum DC Blocking Voltage	VDC	200	400	600	800	1000	1200	V
Maximum Average Forward Rectified Current TC=125°C (Total Device 2x20.0A=40.0A)	IF(AV)	40.0						A
Peak Forward Surge Current, 8.3ms single Half sine-wave superimposed on rated load (JEDEC method)(Per Diode/Per Leg)	IFSM	400						A
Maximum Instantaneous Forward Voltage @20.0A(Per Diode/Per Leg)	VF (Typical)	0.85-1.00	1.00-1.30	1.30-1.70	1.30-1.70			V
Maximum DC Reverse Current @TJ=25°C At Rated DC Blocking Voltage @TJ=125°C	IR	1.0 100						µA µA
Maximum Reverse Recovery Time (Note1)	Trr	35-50			50-75			nS
Typical Junction Capacitance (Note 2)	CJ	200						pF
Typical Thermal Resistance (Note 3)	RθJC	0.75						°C/W
Operating Junction and Storage Temperature Range	TJ,TSTG	-55 to +175						°C

Note:(1)Reverse recovery test conditions IF = 0.5A, IR = 1.0A, Irr = 0.25A.
 Note:(2)Measured at 1.0 MHz and applied reverse voltage of 4.0 Volts DC.
 Note:(3)Thermal Resistance junction to case.

FIG.1 - FORWARD CURRENT DERATING CURVE




FIG.2 - MAXIMUM NON-REPETITIVE PEAK FORWARD SURGE CURRENT




FIG.3 - TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS




FIG.4 - TYPICAL REVERSE CHARACTERISTICS




FIG.5 - TYPICAL JUNCTION CAPACITANCE

