

Pb Free Plating Product

APT30D20BCT/APT30D20BCTG



2*30A/200V Heatsink Dual Cathode Common Ultra Fast Recovery Rectifiers

APPLICATION

- Freewheeling, Snubber, Clamp
- Inversion Welder
- PFC
- Plating Power Supply
- Ultrasonic Cleaner and Welder
- Converter & Chopper
- UPS

PRODUCT FEATURE

- Ultrafast Recovery Time
- Soft Recovery Characteristics
- Low Recovery Loss
- Low Forward Voltage
- High Surge Current Capability
- Low Leakage Current

TO-3PN/TO-3PB-SQ

② Bottom Side Metal Heat Sink (Back of Case-Cathode)

Internal Configuration

Positive Common Cathode	Negative Common Anode	Doubler Tandem Polarity	Series Tandem Polarity
Suffix "CT"	Suffix "CA"	Suffix "CD"	Suffix "HB"
Suffix "CTG"	Suffix "CAG"	Suffix "CDG"	Suffix "HBG"

GENERAL DESCRIPTION

APT30D20BCT/APT30D20BCTG using the latest FRED FAB process(planar passivation pellet) with ultrafast and soft recovery characteristics.

MAXIMUM RATINGS All Ratings Per Leg: T_C = 25°C unless otherwise specified.

Symbol	Characteristic / Test Conditions	APT30D20BCT/APT30D20BCTG	UNIT
V _R	Maximum D.C. Reverse Voltage	200	Volts
V _{RRM}	Maximum Peak Repetitive Reverse Voltage		
V _{RWM}	Maximum Working Peak Reverse Voltage		
I _{F(AV)}	Maximum Average Forward Current (T _C = 145°C, Duty Cycle = 0.5)	30	Amps
I _{F(AV)}	RMS Forward Current (Square wave, 50% duty)	80	
I _{FSM}	Non-Repetitive Forward Surge Current (T _J = 45°C, 8.3ms)	320	
T _J , T _{STG}	Operating and Storage Temperature Range	-55 to 175	°C
T _L	Lead Temperature for 10 Sec.	300	

STATIC ELECTRICAL CHARACTERISTICS

Symbol	Characteristic / Test Conditions	MIN	TYP	MAX	UNIT
V _F	Forward Voltage	I _F = 30A	1.1	1.3	Volts
		I _F = 60A	1.4		
		I _F = 30A, T _J = 125°C	0.9		
I _{RM}	Maximum Reverse Leakage Current	V _R = V _R Rated		250	μA
		V _R = V _R Rated, T _J = 125°C		500	
C _T	Junction Capacitance, V _R = 200V		95		pF

DYNAMIC CHARACTERISTICS

Symbol	Characteristic	Test Conditions	MIN	TYP	MAX	UNIT
t_{rr}	Reverse Recovery Time	$I_F = 1A$, $di_F/dt = -100A/\mu s$, $V_R = 30V$, $T_J = 25^\circ C$	-	21		ns
t_{rr}	Reverse Recovery Time	$I_F = 30A$, $di_F/dt = -200A/\mu s$ $V_R = 133V$, $T_C = 25^\circ C$	-	24		
Q_{rr}	Reverse Recovery Charge		-	33		nC
I_{RRM}	Maximum Reverse Recovery Current		-	3	-	Amps
t_{rr}	Reverse Recovery Time	$I_F = 30A$, $di_F/dt = -200A/\mu s$ $V_R = 133V$, $T_C = 125^\circ C$	-	48		ns
Q_{rr}	Reverse Recovery Charge		-	150		nC
I_{RRM}	Maximum Reverse Recovery Current		-	6	-	Amps
t_{rr}	Reverse Recovery Time	$I_F = 30A$, $di_F/dt = -1000A/\mu s$ $V_R = 133V$, $T_C = 125^\circ C$	-	31		ns
Q_{rr}	Reverse Recovery Charge		-	355		nC
I_{RRM}	Maximum Reverse Recovery Current		-	19		Amps

THERMAL AND MECHANICAL CHARACTERISTICS

Symbol	Characteristic / Test Conditions	MIN	TYP	MAX	UNIT
$R_{\theta JC}$	Junction-to-Case Thermal Resistance			.67	$^\circ C/W$
$R_{\theta JA}$	Junction-to-Ambient Thermal Resistance			40	
W_T	Package Weight		0.22		oz
			5.9		g
Torque	Maximum Mounting Torque			10	lb•in
				1.1	N•m




FIGURE 1a. MAXIMUM EFFECTIVE TRANSIENT THERMAL IMPEDANCE, JUNCTION-TO-CASE vs. PULSE DURATION




FIGURE 1b. TRANSIENT THERMAL IMPEDANCE MODEL

TYPICAL PERFORMANCE CURVES




Figure 2. Forward Current vs. Forward Voltage




Figure 4. Reverse Recovery Charge vs. Current Rate of Change




Figure 6. Dynamic Parameters vs. Junction Temperature




Figure 8. Junction Capacitance vs. Reverse Voltage




Figure 3. Reverse Recovery Time vs. Current Rate of Change




Figure 5. Reverse Recovery Current vs. Current Rate of Change




Figure 7. Maximum Average Forward Current vs. Case Temperature




Figure 9. Diode Test Circuit

- ① I_F - Forward Conduction Current
- ② di_F/dt - Rate of Diode Current Change Through Zero Crossing.
- ③ I_{RRM} - Maximum Reverse Recovery Current.
- ④ t_{rr} - Reverse Recovery Time, measured from zero crossing where diode current goes from positive to negative, to the point at which the straight line through I_{RRM} and $0.25 \cdot I_{RRM}$ passes through zero.
- ⑤ Q_{rr} - Area Under the Curve Defined by I_{RRM} and t_{rr} .





Figure 10, Diode Reverse Recovery Waveform and Definitions

Package Outline

THINKI TO-3PN/TO-3PB-SQ



Symbol	Dimensions(millimeters)	
	Min.	Max.
A	4.60	5.00
A1	1.50	2.00
A2	2.20	2.60
b	0.80	1.20
b1	2.90	3.30
b2	1.90	2.30
c	0.40	0.80
e	5.25	5.65
E	15.3	15.7
E1	13.2	13.6
E2	13.1	13.5
E3	9.10	9.50
H	19.7	20.1
H1	19.1	20.1
H2	18.3	18.7
H3	2.80	3.20
G	4.80	5.20
ΦP	3.00	3.40