

Pb Free Plating Product

D92-02PB




ThinkiSemi Heatsink Dual Common Cathode Ultra Fast Recovery Rectifiers

Features

- Ultrafast Recovery Time
- Soft Recovery Characteristics
- Low Recovery Loss
- Low Forward Voltage
- High Surge Current Capability
- Low Leakage Current

APPLICATIONS

- Freewheeling, Snubber, Clamp
- Inversion Welder
- PFC
- Plating Power Supply
- Ultrasonic Cleaner and Welder
- Converter & Chopper
- UPS



ABSOLUTE MAXIMUM RATINGS

 $T_C=25^{\circ}\text{C}$ unless otherwise specified

Symbol	Parameter	Test Conditions	Values	Unit
V_R	Maximum D.C. Reverse Voltage		220	V
V_{RRM}	Maximum Repetitive Reverse Voltage		220	V
$I_{F(AV)}$	Average Forward Current	$T_C=110^{\circ}\text{C}$, Per Diode	10	A
		$T_C=110^{\circ}\text{C}$, Per Package	20	A
$I_{F(RMS)}$	RMS Forward Current	$T_C=110^{\circ}\text{C}$, Per Diode	14	A
I_{FSM}	Non-Repetitive Surge Forward Current	$T_J=45^{\circ}\text{C}$, $t=10\text{ms}$, 50Hz, Sine	100	A
P_D	Power Dissipation		83	W
T_J	Junction Temperature		-40 to +150	$^{\circ}\text{C}$
T_{STG}	Storage Temperature Range		-40 to +150	$^{\circ}\text{C}$
Torque	Module-to-Sink	Recommended (M3)	1.1	N·m
$R_{\theta JC}$	Thermal Resistance	Junction-to-Case	1.5	$^{\circ}\text{C/W}$
Weight			6.0	g

ELECTRICAL CHARACTERISTICS

 $T_C=25^{\circ}\text{C}$ unless otherwise specified

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Unit
I_{RM}	Reverse Leakage Current	$V_R=220\text{V}$	--	--	50	μA
		$V_R=220\text{V}$, $T_J=125^{\circ}\text{C}$	--	--	1	mA
V_F	Forward Voltage	$I_F=10\text{A}$	--	0.86	0.95	V
		$I_F=10\text{A}$, $T_J=125^{\circ}\text{C}$	--	--	0.80	V
t_{rr}	Reverse Recovery Time	$I_F=1\text{A}$, $V_R=30\text{V}$, $di_F/dt=-200\text{A}/\mu\text{s}$	--	25	--	ns
t_{rr}	Reverse Recovery Time	$V_R=100\text{V}$, $I_F=10\text{A}$	--	32	--	ns
I_{RRM}	Max. Reverse Recovery Current	$di_F/dt=-200\text{A}/\mu\text{s}$, $T_J=25^{\circ}\text{C}$	--	2.1	--	A
t_{rr}	Reverse Recovery Time	$V_R=100\text{V}$, $I_F=10\text{A}$	--	45	--	ns
I_{RRM}	Max. Reverse Recovery Current	$di_F/dt=-200\text{A}/\mu\text{s}$, $T_J=125^{\circ}\text{C}$	--	5	--	A




Fig1. Forward Voltage Drop vs Forward Current





Fig2. Reverse Recovery Time vs di_F/dt Fig3. Reverse Recovery Current vs di_F/dt Fig4. Reverse Recovery Charge vs di_F/dt 

Fig5. Dynamic Parameters vs Junction Temperature





Fig6. Transient Thermal Impedance



Dimensions in Millimeters

THINKI TO-3P/TO-3PB-SQ Package Outline