

Pb Free Plating Product

MUR4020PL thru MUR40120PL



40.0 Ampere Heatsink Dual Series Connection Ultra Fast Recovery Rectifiers

Features ※ ThinkSemi latest&matured process FRD ※ Low forward voltage drop ※ High current capability ※ Low reverse leakage current ※ High surge current capability Application ※ Automotive Inverters and Solar Inverters ※ Car Audio Amplifiers and Sound Device Systems ※ Plating Power Supply, Motor Control, UPS and SMPS etc. Mechanical Data ※ Case: Heatsink open metal TO-3P(TO-3PN/TO-3PB) package ※ Epoxy: UL 94V-0 rate flame retardant ※ Terminals: Solderable per MIL-STD-202 method 208 ※ Polarity: As marked on diode body ※ Mounting position: Any ※ Weight: 6.5 gram approximately	TO-3P(TO-3PN-SQ)
--	-------------------------

FIG.1 - FORWARD CURRENT DERATING CURVE




FIG.2 - MAXIMUM NON-REPETITIVE PEAK FORWARD SURGE CURRENT




FIG.3 - TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS




FIG.4 - TYPICAL REVERSE CHARACTERISTICS




FIG.5 - TYPICAL JUNCTION CAPACITANCE

