

Pb Free Plating Product

MURB1220CS thru MURB12120CS



12.0 Ampere Surface Mount Dual Series Connection Ultra Fast Recovery Rectifiers

Features	TO-263AB/D2PAK	Unit:inch(mm)
※ ThinkSemi latest&matured process FRD/FRED ※ Low forward voltage drop ※ High current capability ※ Low reverse leakage current ※ High surge current capability	① ② ③ ① ② ③ ① ② ③ ① ② ③ Positive Common Cathode Suffix "CT" Negative Common Anode Suffix "CA" Doubler Polarity Suffix "CD" Series Connection Suffix "CS"	
Application		
※ Automotive Inverters and Solar Inverters ※ Car Audio Amplifiers and Sound Device Systems ※ Plating Power Supply, Motor Control, UPS and SMPS etc.		
Mechanical Data		
※ Case: Surface Mount TO-263AB/D2PAK package ※ Epoxy: UL 94V-0 rate flame retardant ※ Terminals: Solderable per MIL-STD-202 method 208 ※ Polarity: As marked on diode body ※ Mounting position: Any ※ Weight: 1.8 gram approximately		

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Rating at 25°C ambient temperature unless otherwise specified.

Single phase, half wave, 60Hz, resistive or inductive load.

For capacitive load, derate current by 20%.

PARAMETER	SYMBOL	MURB1220CS	MURB1230CS MURB1240CS	MURB1260CS	MURB1280CS	MURB12100CS	MURB12120CS	UNIT
Maximum Recurrent Peak Reverse Voltage	VRRM	200	400	600	800	1000	1200	V
Maximum RMS Voltage	VRMS	140	280	420	560	700	840	V
Maximum DC Blocking Voltage	VDC	200	400	600	800	1000	1200	V
Maximum Average Forward Rectified Current TC=125℃ (Total Device 2x6.0A=12.0A)	IF(AV)	12.0						A
Peak Forward Surge Current, 8.3ms single Half sine-wave superimposed on rated load (JEDEC method)(Per Diode/Per Leg)	IFSM	125						A
Maximum Instantaneous Forward Voltage @6.0A(Per Diode/Per Leg)	VF (Typical)	0.90-1.10	1.10-1.40	1.40-1.80	1.40-1.80			V
Maximum DC Reverse Current @TJ=25℃ At Rated DC Blocking Voltage @TJ=125℃	IR	5.0 500					μA μA	
Maximum Reverse Recovery Time (Note1)	Trr	35-50			50-75			nS
Typical Junction Capacitance (Note 2)	CJ	65					pF	
Typical Thermal Resistance (Note 3)	RθJC	2.0						℃/W
Operating Junction and Storage Temperature Range	TJ,TSTG	-55 to +175						℃

Note:(1)Reverse recovery test conditions IF = 0.5A, IR = 1.0A, Irr = 0.25A.

Note:(2)Measured at 1.0 MHz and applied reverse voltage of 4.0 Volts DC.

Note:(3)Thermal Resistance junction to case.

FIG.1 - FORWARD CURRENT DERATING CURVE




FIG.2 - MAXIMUM NON-REPETITIVE PEAK FORWARD SURGE CURRENT




FIG.3 - TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS




FIG.4 - TYPICAL REVERSE CHARACTERISTICS




FIG.5 - TYPICAL JUNCTION CAPACITANCE

