

Pb Free Plating Product

TUR2520GR



25.0 Ampere Heatsink Package Negative Ultra Fast Recovery Rectifier Diode

Features	TO-220AC(TO-220-2L) Unit:inch(mm)
※ ThinkSemi latest&matured process FRED ※ Low forward voltage drop ※ High current capability ※ Low reverse leakage current ※ High surge current capability	Internal Configuration ① Base Backside ② Base Backside ③ Base Backside Positive Suffix "G" Negative Suffix "GR"
Application	
※ Automotive Inverters and Solar Inverters ※ Car Audio Amplifiers and Sound Device Systems ※ Plating Power Supply, Motor Control, UPS and SMPS etc.	
Mechanical Data	
※ Case: TO-220AC(TO-220-2L) with heat sink package ※ Epoxy: UL 94V-0 rate flame retardant ※ Terminals: Solderable per MIL-STD-202 method 208 ※ Polarity: As marked on diode body ※ Mounting position: Any ※ Weight: 2.0 gram approximately	

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Rating at 25°C ambient temperature unless otherwise specified.

Single phase, half wave, 60Hz, resistive or inductive load.

For capacitive load, derate current by 20%.

PARAMETER	SYMBOL	TUR2520GR	UNIT
Maximum Recurrent Peak Reverse Voltage	VRRM	200	V
Maximum RMS Voltage	VRMS	140	V
Maximum DC Blocking Voltage	VDC	200	V
Maximum Average Forward Rectified Current TC=125°C (Total Device 25A)	IF(AV)	25	A
Peak Forward Surge Current, 8.3ms single Half sine-wave superimposed on rated load (JEDEC method)(Per Diode/Per Leg)	IFSM	300	A
Maximum Instantaneous Forward Voltage @25A(Per Diode/Per Leg)	VF (Typical)	0.90-1.05	V
Maximum DC Reverse Current @TJ=25°C At Rated DC Blocking Voltage @TJ=125°C	IR	1.0 100	μA μA
Maximum Reverse Recovery Time (Note1)	Trr	15-25	nS
Typical Junction Capacitance (Note 2)	CJ	200	pF
Typical Thermal Resistance (Note 3)	RθJC	1.5	°C/W
Operating Junction and Storage Temperature Range	TJ,TSTG	-55 to +175	°C

Note:(1)Reverse recovery test conditions IF = 0.5A, IR = 1.0A, Irr = 0.25A.

Note:(2)Measured at 1.0 MHz and applied reverse voltage of 4.0 Volts DC.

Note:(3)Thermal Resistance junction to case.

FIG.1 - FORWARD CURRENT DERATING CURVE




FIG.2 - MAXIMUM NON-REPETITIVE PEAK FORWARD SURGE CURRENT




FIG.3 - TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS




FIG.4 - TYPICAL REVERSE CHARACTERISTICS




FIG.5 - TYPICAL JUNCTION CAPACITANCE

